CAPPUCCINO #EU35953F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 3/20/2018 Revision date: 2/8/2024 Supersedes version of: 9/17/2023 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	:	Mixture
Trade name	:	CAPPUCCINO #EU35953F
UFI	:	ARJ6-93EW-M001-AJUF
Product code	:	EU35953F
Type of product	:	Perfumes, fragrances
Product group	:	Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category	:	Professional use,Industrial use
Industrial/Professional use spec	:	Industrial For professional use only
Use of the substance/mixture	:	Perfumes, fragrances
Function or use category	:	Odour agents

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

FRENCH COLOR & FRAGRANCE International GmbH
Mittlerer Weg 35
DE 79424 Auggen
Germany
T 49-7631-931-8900
SDS@frenchcolor.com, www.frenchcolor.com

1.4. Emergency telephone number

Emergency number	:	1-800-255-3924; +01-813-248-0585; China:+400-120-0751; Mexico:+01-800-099-0731; Brazil: +0-800-591-6042; India: +000-800-100-4086

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin sensitisation, Category 1 H317
Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

May cause an allergic skin reaction.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :

GHS07

Signal word (CLP)	:	Warning
Contains	:	Heliotropine; COUMARIN; 1,2-Cyclopentanedione, 3-methyl-; 3(2H)-Furanone, 4-hydroxy-2,5-dimethyl-
Hazard statements (CLP)	:	H317 - May cause an allergic skin reaction.

Precautionary statements (CLP)	:	P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P272 - Contaminated work clothing should not be allowed out of the workplace. P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P302+P352 - IF ON SKIN: Wash with plenty of water. P321 - Specific treatment (see supplemental first aid instruction on this label). P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
Extra phrases	:	Restricted to professional users. For professional users only.

2.3. Other hazards

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Bis(2-ethylhexyl) adipate substance with national workplace exposure limit(s) (PL)	CAS-No.: 103-23-1 EC-No.: 203-090-1 REACH-no: 01-2119439699-19	44.25 – 88.5	Not classified
Ethyl vanillin	CAS-No.: 121-32-4 EC-No.: 204-464-7 REACH-no: 01-211958961-24	1.875 – 3.75	Eye Irrit. 2, H319
COUMARIN	CAS-No.: 91-64-5 EC-No.: 202-086-7 REACH-no: 01-2119943756-26	0.95 – 1.9	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Skin Sens. 1, H317 Aquatic Chronic 2, H411
1,2-Cyclopentanedione, 3-methyl-	CAS-No.: 765-70-8 EC-No.: 212-154-8	0.75 – 1.5	Acute Tox. 4 (Oral), H302 Skin Sens. 1, H317
Vanillin	CAS-No.: 121-33-5 EC-No.: 204-465-2 REACH-no: 01-2119516040-60	0.6506075 – 1.30243	Eye Irrit. 2, H319
Heliotropine	CAS-No.: 120-57-0 EC-No.: 204-409-7 REACH-no: 01-2119983608-21	0.375 – 0.75	Skin Sens. 1B, H317
benzyl benzoate	CAS-No.: 120-51-4 EC-No.: 204-402-9 EC Index-No.: 607-085-00-9 REACH-no: 01-2119976371-33	0.0484245 – 0.193698	Acute Tox. 4 (Oral), H302 Aquatic Acute 1, H400 Aquatic Chronic 2, H411

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
3(2H)-Furanone, 4-hydroxy-2,5-dimethyl-	CAS-No.: 3658-77-3 EC-No.: 222-908-8	0.00678 – 0.02712	Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Eye Irrit. 2, H319 Skin Sens. 1A, H317
Acetyl Propionyl substance with national workplace exposure limit(s) (DE, SI, CH)	CAS-No.: 600-14-6 EC-No.: 209-984-8	0.00507 – 0.02028	Flam. Liq. 2, H225 Eye Dam. 1, H318 Skin Sens. 1B, H317 STOT RE 2, H373
ethanol; ethyl alcohol substance with national workplace exposure limit(s) (AT, BE, BG, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, LT, LV, NL, PL, PT, RO, SE, SI, SK, NO, CH)	CAS-No.: 64-17-5 EC-No.: 200-578-6 EC Index-No.: 603-002-00-5	0.00015 – 0.00636	Flam. Liq. 2, H225
pyridine substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 110-86-1 EC-No.: 203-809-9 EC Index-No.: 613-002-00-7	0.0003075 – 0.00123	Flam. Liq. 2, H225 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:dust,mist), H332
2,6-xylenol substance with national workplace exposure limit(s) (LV, RO)	CAS-No.: 576-26-1 EC-No.: 209-400-1 EC Index-No.: 604-006-00-X	0.0002475 – 0.00099	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Skin Corr. 1B, H314 Eye Dam. 1, H318 Aquatic Chronic 2, H411
Isovaleraldehyde substance with national workplace exposure limit(s) (AT, DE, LT, SI)	CAS-No.: 590-86-3 EC-No.: 209-691-5	0.0001875 – 0.00075	Flam. Liq. 2, H225 Eye Irrit. 2, H319 Skin Sens. 1B, H317 STOT SE 3, H335 Aquatic Chronic 2, H411
acetaldehyde; ethanal substance with national workplace exposure limit(s) (AT, BE, BG, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, LT, LV, NL, PL, PT, RO, SE, SI, SK, NO, CH)	CAS-No.: 75-07-0 EC-No.: 200-836-8 EC Index-No.: 605-003-00-6	0.000075 – 0.0003	Flam. Liq. 1, H224 Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319 Muta. 2, H341 Carc. 1B, H350 STOT SE 3, H335

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. Allow the victim to rest.

First-aid measures after skin contact : Wash with plenty of water/…. If skin irritation or rash occurs: Get medical advice/attention. Specific treatment (see supplemental first aid instruction on this label). Wash contaminated clothing before reuse. Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation occurs: Get medical advice/attention. Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists. Rinse eyes with water as a precaution.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Not expected to present a significant hazard under anticipated conditions of normal use.
Symptoms/effects after inhalation : May cause an allergic skin reaction.
Symptoms/effects after skin contact : May cause an allergic skin reaction.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Sand. Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Evacuate unnecessary personnel. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures : Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

See Section 8. Exposure controls and personal protection. For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Wear personal protective equipment.

Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container closed when not in use. Store in a well-ventilated place. Keep cool.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight.

Storage temperature : 25 °C

Storage area : Store in a well-ventilated place. Store away from heat.

Special rules on packaging : Store in a closed container.

Packaging materials : Do not store in corrodable metal.

Switzerland

Storage class (LK) : LK 10/12 - Liquids

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Bis(2-ethylhexyl) adipate (103-23-1)	
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	400 mg/m³

acetaldehyde; ethanal (75-07-0)	
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	90 mg/m³
	50 ppm
MAK (OEL STEL)	90 mg/m³
	50 ppm
OEL C	90 mg/m³
	50 ppm
OEL chemical category	Group B Carcinogen
Belgium - Occupational Exposure Limits	
OEL TWA	25 ppm
Bulgaria - Occupational Exposure Limits	
OEL TWA	30 mg/m³
OEL STEL	200 mg/m³

acetaldehyde; ethanal (75-07-0)	
Croatia - Occupational Exposure Limits	
GVI (OEL TWA)	37 mg/m³
	20 ppm
KGVI (OEL STEL)	92 mg/m³
	50 ppm
Czech Republic - Occupational Exposure Limits	
PEL (OEL TWA)	50 mg/m³
Denmark - Occupational Exposure Limits	
OEL C	45 mg/m³
	25 ppm
Estonia - Occupational Exposure Limits	
OEL TWA	45 mg/m³
	25 ppm
OEL STEL	90 mg/m³
	50 ppm
OEL chemical category	Carcinogenic substance
Finland - Occupational Exposure Limits	
HTP (OEL STEL)	46 mg/m³
	25 ppm
France - Occupational Exposure Limits	
VME (OEL TWA)	180 mg/m³
	100 ppm
OEL chemical category	Carcinogen category 1B, Mutagen category 2
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA)	91 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
	50 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Greece - Occupational Exposure Limits	
OEL TWA	180 mg/m³
	100 ppm
OEL STEL	270 mg/m³
	150 ppm
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	45 mg/m³
CK (OEL STEL)	45 mg/m³
Ireland - Occupational Exposure Limits	
OEL STEL	45 mg/m³
	25 ppm

acetaldehyde; ethanal (75-07-0)	
Latvia - Occupational Exposure Limits	
OEL TWA	5 mg/m³
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	45 mg/m³
	25 ppm
TPRV (OEL STEL)	90 mg/m³
	50 ppm
OEL chemical category	Carcinogen
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	37 mg/m³
	20 ppm
TGG-15min (OEL STEL)	92 mg/m³
	50 ppm
Poland - Occupational Exposure Limits	
NDSP (OEL C)	45 mg/m³
Portugal - Occupational Exposure Limits	
OEL C	25 ppm
OEL chemical category	A2 - Suspected Human Carcinogen
Romania - Occupational Exposure Limits	
OEL TWA	90 mg/m³
	50 ppm
OEL STEL	180 mg/m³
	100 ppm
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA)	91 mg/m³
	50 ppm
Slovenia - Occupational Exposure Limits	
OEL TWA	91 mg/m³
	50 ppm
OEL STEL	91 mg/m³
	50 ppm
OEL chemical category	Category 2
Spain - Occupational Exposure Limits	
VLA-EC (OEL STEL)	46 mg/m³
	25 ppm
OEL chemical category	C1B
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	45 mg/m³
	25 ppm

acetaldehyde; ethanal (75-07-0)	
KGV (OEL STEL)	90 mg/m³
	50 ppm
OEL chemical category	Carcinogen
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	37 mg/m³
	20 ppm
WEL STEL (OEL STEL)	92 mg/m³
	50 ppm
WEL chemical category	Capable of causing cancer and/or heritable genetic damage
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA)	45 mg/m³
	25 ppm
Korttidsverdi (OEL STEL)	67.5 mg/m³ (value calculated)
	37.5 ppm (value calculated)
OEL chemical category	Carcinogen
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA)	90 mg/m³
	50 ppm
KZGW (OEL STEL)	90 mg/m³
	50 ppm
OEL chemical category	Category C2 carcinogen
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL C	25 ppm
ACGIH chemical category	Suspected Human Carcinogen

ethanol; ethyl alcohol (64-17-5)	
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	1900 mg/m³
	1000 ppm
MAK (OEL STEL)	3800 mg/m³
	2000 ppm
Belgium - Occupational Exposure Limits	
OEL TWA	1907 mg/m³
	1000 ppm
Bulgaria - Occupational Exposure Limits	
OEL TWA	1000 mg/m³
Croatia - Occupational Exposure Limits	
GVI (OEL TWA)	1900 mg/m³
	1000 ppm

ethanol; ethyl alcohol (64-17-5)	
Czech Republic - Occupational Exposure Limits	
PEL (OEL TWA)	1000 mg/m³
Denmark - Occupational Exposure Limits	
OEL TWA	1900 mg/m³
	1000 ppm
OEL STEL	3800 mg/m³
	2000 ppm
Estonia - Occupational Exposure Limits	
OEL TWA	1000 mg/m³
	500 ppm
OEL STEL	1900 mg/m³
	1000 ppm
Finland - Occupational Exposure Limits	
HTP (OEL TWA)	1900 mg/m³
	1000 ppm
HTP (OEL STEL)	2500 mg/m³
	1300 ppm
France - Occupational Exposure Limits	
VME (OEL TWA)	1900 mg/m³
	1000 ppm
VLE (OEL C/STEL)	9500 mg/m³
	5000 ppm
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA)	380 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
	200 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Greece - Occupational Exposure Limits	
OEL TWA	1900 mg/m³
	1000 ppm
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	1900 mg/m³
CK (OEL STEL)	3800 mg/m³
Ireland - Occupational Exposure Limits	
OEL STEL	1000 ppm
Latvia - Occupational Exposure Limits	
OEL TWA	1000 mg/m³
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	1000 mg/m³
	500 ppm

ethanol; ethyl alcohol (64-17-5)	
TPRV (OEL STEL)	1900 mg/m³
	1000 ppm
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	260 mg/m³
	137 ppm
TGG-15min (OEL STEL)	1900 mg/m³
	1000 ppm
MAC chemical category	Skin notation
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	1900 mg/m³
Portugal - Occupational Exposure Limits	
OEL STEL	1000 ppm
OEL chemical category	A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans
Romania - Occupational Exposure Limits	
OEL TWA	1900 mg/m³
	1000 ppm
OEL STEL	9500 mg/m³
	5000 ppm
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA)	960 mg/m³
	500 ppm
NPHV (OEL C)	1920 mg/m³
Slovenia - Occupational Exposure Limits	
OEL TWA	960 mg/m³
	500 ppm
OEL STEL	1920 mg/m³
	1000 ppm
Spain - Occupational Exposure Limits	
VLA-EC (OEL STEL)	1910 mg/m³
	1000 ppm
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	1000 mg/m³
	500 ppm
KGV (OEL STEL)	1900 mg/m³
	1000 ppm
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	1920 mg/m³
	1000 ppm
WEL STEL (OEL STEL)	5760 mg/m³ (calculated)

ethanol; ethyl alcohol (64-17-5)	
	3000 ppm (calculated)
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA)	950 mg/m³
	500 ppm
Korttidsverdi (OEL STEL)	1187.5 mg/m³ (value calculated)
	625 ppm (value calculated)
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA)	960 mg/m³
	500 ppm
KZGW (OEL STEL)	1920 mg/m³
	1000 ppm
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL STEL	1000 ppm
ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans

Acetyl Propionyl (600-14-6)	
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA)	0.083 mg/m³
	0.02 ppm
Chemical category	Skin notation, Skin sensitization
Slovenia - Occupational Exposure Limits	
OEL TWA	0.083 mg/m³
	0.02 ppm
OEL STEL	0.083 mg/m³
	0.02 ppm
OEL chemical category	Potential for cutaneous absorption
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA)	0.08 mg/m³
	0.02 ppm
KZGW (OEL STEL)	0.16 mg/m³
	0.04 ppm
OEL chemical category	Sensitizer, Skin notation

Isovaleraldehyde (590-86-3)	
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	39 mg/m³
	10 ppm
MAK (OEL STEL)	39 mg/m³
	10 ppm
OEL C	39 mg/m³

Isovaleraldehyde (590-86-3)	
	10 ppm
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA)	39 mg/m³
	10 ppm
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	10 mg/m³
Slovenia - Occupational Exposure Limits	
OEL TWA	39 mg/m³
	10 ppm
OEL STEL	39 mg/m³
	10 ppm

pyridine (110-86-1)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	15 mg/m³ (existing scientific data on health effects appear to be particularly limited)
	5 ppm (existing scientific data on health effects appear to be particularly limited)
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	15 mg/m³
	5 ppm
MAK (OEL STEL)	60 mg/m³
	20 ppm
OEL chemical category	Skin notation
Belgium - Occupational Exposure Limits	
OEL TWA	3.3 mg/m³
	1 ppm
Bulgaria - Occupational Exposure Limits	
OEL TWA	15 mg/m³
Croatia - Occupational Exposure Limits	
GVI (OEL TWA)	15 mg/m³
	5 ppm
Cyprus - Occupational Exposure Limits	
OEL TWA	15 mg/m³
	5 ppm
Czech Republic - Occupational Exposure Limits	
PEL (OEL TWA)	5 mg/m³
OEL chemical category	Potential for cutaneous absorption
Denmark - Occupational Exposure Limits	
OEL TWA	15 mg/m³
	5 ppm
OEL STEL	30 mg/m³

pyridine (110-86-1)	
	10 ppm
Estonia - Occupational Exposure Limits	
OEL TWA	15 mg/m³
	5 ppm
Finland - Occupational Exposure Limits	
HTP (OEL TWA)	3 mg/m³
	1 ppm
HTP (OEL STEL)	16 mg/m³
	5 ppm
OEL chemical category	Potential for cutaneous absorption
France - Occupational Exposure Limits	
VME (OEL TWA)	15 mg/m³
	5 ppm
VLE (OEL C/STEL)	30 mg/m³
	10 ppm
Gibraltar - Occupational Exposure Limits	
OEL TWA	15 mg/m³ (existing scientific data on health effects appear to be particularly limited)
	5 ppm (existing scientific data on health effects appear to be particularly limited)
Greece - Occupational Exposure Limits	
OEL TWA	15 mg/m³
	5 ppm
OEL STEL	30 mg/m³
	10 ppm
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	15 mg/m³
CK (OEL STEL)	30 mg/m³
OEL chemical category	Sensitizer, Potential for cutaneous absorption
Ireland - Occupational Exposure Limits	
OEL TWA	15 mg/m³
	5 ppm
OEL STEL	30 mg/m³
	10 ppm (total resin acid-airborne)
Latvia - Occupational Exposure Limits	
OEL TWA	15 mg/m³
	5 ppm
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	15 mg/m³
	5 ppm

pyridine (110-86-1)	
Luxembourg - Occupational Exposure Limits	
OEL TWA	15 mg/m³
	5 ppm
Malta - Occupational Exposure Limits	
OEL TWA	15 mg/m³
	5 ppm
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	0.9 mg/m³
	0.3 ppm
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	5 mg/m³
Portugal - Occupational Exposure Limits	
OEL TWA	15 mg/m³ (indicative limit value)
	5 ppm (indicative limit value)
OEL chemical category	A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans
Romania - Occupational Exposure Limits	
OEL TWA	15 mg/m³
	5 ppm
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA)	15 mg/m³
	5 ppm
Slovenia - Occupational Exposure Limits	
OEL TWA	15 mg/m³
	5 ppm
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA)	3 mg/m³
	1 ppm
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	7 mg/m³
	2 ppm
KGV (OEL STEL)	10 mg/m³
	3 ppm
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	16 mg/m³
	5 ppm
WEL STEL (OEL STEL)	33 mg/m³
	10 ppm
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA)	15 mg/m³

pyridine (110-86-1)	
	5 ppm
Korttidsverdi (OEL STEL)	22.5 mg/m³ (value calculated)
	10 ppm (value calculated)
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA)	15 mg/m³
	5 ppm
KZGW (OEL STEL)	30 mg/m³
	10 ppm
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	1 ppm
ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans

2,6-xylenol (576-26-1)	
Latvia - Occupational Exposure Limits	
OEL TWA	2 mg/m³
Romania - Occupational Exposure Limits	
OEL TWA	15 mg/m³
OEL STEL	20 mg/m³
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	1 ppm (inhalable fraction and vapor)
ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans, dermal sensitizer

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:
Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:
Avoid all unnecessary exposure.

Personal protective equipment symbol(s):

8.2.2.1. Eye and face protection

Eye protection:
Chemical goggles or safety glasses. Safety glasses

8.2.2.2. Skin protection

Skin and body protection:
Wear suitable protective clothing

Hand protection:
Wear protective gloves.

8.2.2.3. Respiratory protection

Respiratory protection:
Wear appropriate mask

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:
Avoid release to the environment.

Other information:
Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	:	Liquid
Colour	:	light yellow. amber. Conforms to standard.
Odour	:	characteristic.
Odour threshold	:	Not available
Melting point	:	Not applicable
Freezing point	:	Not available
Boiling point	:	Not available
Flammability	:	Not applicable
Lower explosion limit	:	Not available
Upper explosion limit	:	Not available
Flash point	:	> 93.33 °C (closed cup) ASTM D7094
Auto-ignition temperature	:	Not available
Decomposition temperature	:	Not available
pH	:	Not available
Viscosity, kinematic	:	Not available
Solubility	:	Not available
Partition coefficient n-octanol/water (Log Kow)	:	Not available
Vapour pressure	:	Not available
Vapour pressure at 50°C	:	Not available
Density	:	Not available
Relative density	:	≈ 1
Relative vapour density at 20°C	:	Not available
Particle characteristics	:	Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Bis(2-ethylhexyl) adipate (103-23-1)	
LD50 oral rat	5600 mg/kg (Source: NLM_CIP)
LD50 dermal rabbit	8410 mg/kg (Source: NLM_CIP)
LC50 Inhalation - Rat	> 5.7 mg/l/4h

Ethyl vanillin (121-32-4)	
LD50 oral rat	1590 mg/kg (Source: NLM_CIP)
LD50 oral	3000 mg/kg bodyweight
LD50 dermal rat	> 2000 mg/kg (Source: ECHA_API)

Heliotropine (120-57-0)	
LD50 oral rat	2700 mg/kg (Source: NLM_CIP)
LD50 oral	2700 mg/kg bodyweight
LD50 dermal rat	> 5000 mg/kg (Source: ECHA_API)

Vanillin (121-33-5)	
LD50 dermal rabbit	> 5010 mg/kg (Source: OECD_SIDS)
LD50 dermal	2600 mg/kg bodyweight

COUMARIN (91-64-5)	
LD50 oral rat	> 5000 mg/kg (Source: JAPAN_GHS)
LD50 oral	290 mg/kg bodyweight
LD50 dermal rat	293 mg/kg (Source: ECHA_API)

1,2-Cyclopentanedione, 3-methyl- (765-70-8)	
LD50 oral	1067 mg/kg bodyweight

acetaldehyde; ethanal (75-07-0)	
LD50 oral rat	660 mg/kg (Source: JAPAN_GHS)
LD50 oral	700 mg/kg bodyweight
LD50 dermal rabbit	3540 mg/kg (Source: NLM_HSDB)
LD50 dermal	3540 mg/kg bodyweight
LC50 Inhalation - Rat [ppm]	13000 ppm/4h

ethanol; ethyl alcohol (64-17-5)	
LD50 oral rat	7060 mg/kg (Source: NLM_CIP)
LC50 Inhalation - Rat	133.8 mg/l/4h

Acetyl Propionyl (600-14-6)	
LD50 oral rat	3 g/kg (Source: NLM_CIP)
LD50 oral	3000 mg/kg bodyweight
LD50 dermal rabbit	> 2000 mg/kg (Source: NIOSH)
LD50 dermal	2500 mg/kg bodyweight

benzyl benzoate (120-51-4)	
LD50 oral rat	500 mg/kg (Source: NLM_CIP)
LD50 oral	1160 mg/kg bodyweight
LD50 dermal rabbit	4000 mg/kg (Source: NLM_CIP)

3(2H)-Furanone, 4-hydroxy-2,5-dimethyl- (3658-77-3)	
LD50 oral	1608 mg/kg bodyweight

Isovaleraldehyde (590-86-3)	
LD50 oral rat	5600 mg/kg (Source: NLM_CIP)
LD50 dermal rabbit	2730 mg/kg (Source: NLM_CIP)
LD50 dermal	2534 mg/kg bodyweight
LC50 Inhalation - Rat	42.7 mg/l/4h

pyridine (110-86-1)	
LD50 oral rat	866 mg/kg (Source: JAPAN_GHS)
LD50 oral	500 mg/kg bodyweight
LD50 dermal rabbit	1000 – 2000 mg/kg (Source: CHEMVIEW)
LD50 dermal	1100 mg/kg bodyweight
LC50 Inhalation - Rat	12.898 mg/l/4h
LC50 Inhalation - Rat (Vapours)	15 mg/l/4h

2,6-xylenol (576-26-1)	
LD50 oral rat	296 mg/kg (Source: JAPAN_GHS)
LD50 oral	296 mg/kg bodyweight
LD50 dermal rabbit	1 g/kg (Source: NLM_CIP)

2,6-xylenol (576-26-1)	
LD50 dermal	960 mg/kg bodyweight

Skin corrosion/irritation : Not classified

pyridine (110-86-1)	
pH	8.5 (conc: 0.2 M (aqueous solution)

Serious eye damage/irritation : Not classified

pyridine (110-86-1)	
pH	8.5 (conc: 0.2 M (aqueous solution)

Respiratory or skin sensitisation : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Bis(2-ethylhexyl) adipate (103-23-1)	
IARC group	3 - Not classifiable

COUMARIN (91-64-5)	
IARC group	3 - Not classifiable

acetaldehyde; ethanal (75-07-0)	
IARC group	1 - Carcinogenic to humans,2B - Possibly carcinogenic to humans

pyridine (110-86-1)	
IARC group	2B - Possibly carcinogenic to humans

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

acetaldehyde; ethanal (75-07-0)	
STOT-single exposure	May cause respiratory irritation.

Isovaleraldehyde (590-86-3)	
STOT-single exposure	May cause respiratory irritation.

STOT-repeated exposure : Not classified

Acetyl Propionyl (600-14-6)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified

Heliotropine (120-57-0)	
Viscosity, kinematic	Not applicable

benzyl benzoate (120-51-4)	
Viscosity, kinematic	7.456 mm²/s

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

No additional information available

11.2.2. Other information

Potential adverse human health effects and symptoms : Based on available data, the classification criteria are not met

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short–term (acute) : Not classified

Hazardous to the aquatic environment, long–term (chronic) : Not classified

Bis(2-ethylhexyl) adipate (103-23-1)	
LC50 - Fish [1]	0.48 – 0.85 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static] Source: EPA)
LC50 - Fish [2]	0.48 – 0.85 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static] Source: EPA)
EC50 - Crustacea [1]	> 1.6 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 72h - Algae [1]	> 500 mg/l (Species: Desmodesmus subspicatus)

Ethyl vanillin (121-32-4)	
LC50 - Fish [1]	81.4 – 94.3 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)

Heliotropine (120-57-0)	
LC50 - Fish [1]	2.5 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [static] Source: ECHA)

Vanillin (121-33-5)	
LC50 - Fish [1]	53 – 61.3 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
LC50 - Fish [2]	88 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: EPA)
NOEC (acute)	10000 mg/kg (Exposure time: 42 Days - Species: Eisenia foetida [soil dry weight])

acetaldehyde; ethanal (75-07-0)	
LC50 - Fish [1]	28 – 34 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
LC50 - Fish [2]	53 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static] Source: EPA)
EC50 - Crustacea [1]	3.64 – 6.15 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
EC50 - Crustacea [2]	48.3 mg/l (Exposure time: 48 h - Species: Daphnia magna)

ethanol; ethyl alcohol (64-17-5)	
LC50 - Fish [2]	> 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: EPA)
EC50 - Crustacea [1]	9268 – 14221 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 - Crustacea [2]	2 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])

benzyl benzoate (120-51-4)	
LC50 - Fish [1]	2.32 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static] Source: ECHA)
NOEC (chronic)	0.168 mg/l

Isovaleraldehyde (590-86-3)	
LC50 - Fish [1]	2.98 – 3.54 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
EC50 - Crustacea [1]	177 mg/l (Exposure time: 48 h - Species: Daphnia magna)

Isovaleraldehyde (590-86-3)	
EC50 72h - Algae [1]	80 mg/l (Species: Desmodesmus subspicatus)
EC50 96h - Algae [1]	78 mg/l (Species: Desmodesmus subspicatus)

pyridine (110-86-1)	
LC50 - Fish [1]	63.4 – 73.6 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
LC50 - Fish [2]	26 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [semi-static] Source: EPA)

2,6-xylenol (576-26-1)	
LC50 - Fish [1]	27 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
EC50 - Crustacea [1]	11.2 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 - Crustacea [2]	11.2 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])

12.2. Persistence and degradability

CAPPUCCINO #EU35953F	
Persistence and degradability	Not established.

Bis(2-ethylhexyl) adipate (103-23-1)	
Persistence and degradability	Rapidly degradable

Ethyl vanillin (121-32-4)	
Persistence and degradability	Rapidly degradable

Heliotropine (120-57-0)	
Persistence and degradability	Rapidly degradable

Vanillin (121-33-5)	
Persistence and degradability	Rapidly degradable

COUMARIN (91-64-5)	
Persistence and degradability	Rapidly degradable

1,2-Cyclopentanedione, 3-methyl- (765-70-8)	
Persistence and degradability	Rapidly degradable

acetaldehyde; ethanal (75-07-0)	
Persistence and degradability	Rapidly degradable

ethanol; ethyl alcohol (64-17-5)	
Persistence and degradability	Rapidly degradable

Acetyl Propionyl (600-14-6)	
Persistence and degradability	Rapidly degradable

benzyl benzoate (120-51-4)	
Persistence and degradability	May cause long-term adverse effects in the environment.

3(2H)-Furanone, 4-hydroxy-2,5-dimethyl- (3658-77-3)	
Persistence and degradability	Rapidly degradable

Isovaleraldehyde (590-86-3)	
Persistence and degradability	Rapidly degradable

pyridine (110-86-1)	
Persistence and degradability	Rapidly degradable

2,6-xylenol (576-26-1)	
Persistence and degradability	Rapidly degradable

12.3. Bioaccumulative potential

CAPPUCCINO #EU35953F	
Bioaccumulative potential	Not established.

Bis(2-ethylhexyl) adipate (103-23-1)	
BCF - Fish [1]	(27 dimensionless)
Partition coefficient n-octanol/water (Log Pow)	8.94 (at 25 °C)

Ethyl vanillin (121-32-4)	
Partition coefficient n-octanol/water (Log Pow)	1.61 (at 25 °C)

Heliotropine (120-57-0)	
Partition coefficient n-octanol/water (Log Pow)	1.2 (at 35 °C)

Vanillin (121-33-5)	
Partition coefficient n-octanol/water (Log Pow)	1.23 (at 22 °C)

acetaldehyde; ethanal (75-07-0)	
Partition coefficient n-octanol/water (Log Pow)	0.45 – 0.63 (at 25 °C (at pH 7)

ethanol; ethyl alcohol (64-17-5)	
Partition coefficient n-octanol/water (Log Pow)	-0.35 (at 24 °C (at pH 7.4)

benzyl benzoate (120-51-4)	
Partition coefficient n-octanol/water (Log Pow)	3.97 (at 25 °C)
Bioaccumulative potential	Not established.

3(2H)-Furanone, 4-hydroxy-2,5-dimethyl- (3658-77-3)	
Partition coefficient n-octanol/water (Log Pow)	0.95 (at 20 °C (at pH 2.5)

Isovaleraldehyde (590-86-3)	
Partition coefficient n-octanol/water (Log Pow)	1.5 (at 25 °C (at pH 7)

pyridine (110-86-1)	
Partition coefficient n-octanol/water (Log Pow)	0.65

2,6-xylenol (576-26-1)	
Partition coefficient n-octanol/water (Log Pow)	2.36

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

Additional information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Product/Packaging disposal recommendations : Dispose of contents/container in accordance with local/national laws and regulations. Dispose in a safe manner in accordance with local/national regulations.

Ecological information : Avoid release to the environment.

HP Code : HP4 - "Irritant – skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shipping name				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available				

14.6. Special precautions for user

Overland transport
Not applicable

Transport by sea
Not applicable

Air transport
Not applicable

Inland waterway transport
Not applicable

Rail transport
Not applicable

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)		
Reference code	**Applicable on**	**Entry title or description**
28.	acetaldehyde; ethanal	Substances which are classified as carcinogen category 1A or 1B in Part 3 of Annex VI to Regulation (EC) No 1272/2008 and are listed in Appendix 1 or Appendix 2, respectively.
3(a)	acetaldehyde; ethanal ; ethanol; ethyl alcohol ; Acetyl Propionyl ; Isovaleraldehyde ; pyridine	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F
3(b)	CAPPUCCINO #EU35953F ; acetaldehyde; ethanal ; Acetyl Propionyl ; benzyl benzoate ; 3(2H)-Furanone, 4-hydroxy-2,5-dimethyl- ; Isovaleraldehyde ; pyridine	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	benzyl benzoate ; Isovaleraldehyde	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1
40.	acetaldehyde; ethanal ; ethanol; ethyl alcohol ; Acetyl Propionyl ; Isovaleraldehyde ; pyridine	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Dual-Use Regulation (428/2009)

Contains no substance subject to the COUNCIL REGULATION (EC) No 428/2009 of 5 May 2009 setting up a Community regime for the control of exports, transfer, brokering and transit of dual-use items.

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Name	CN designation	CAS-No.	CN code	Category, Subcategory	Threshold	Annex
Piperonal		120-57-0	2932 93 00	Category 1		Annex I

15.1.2. National regulations

France

Occupational diseases	
Code	Description
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

Germany

Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1).
Hazardous Incident Ordinance (12. BImSchV) : Is not subject to the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

ABM category : A(2) - toxic for aquatic organisms, may have longterm hazardous effects in aquatic environment
SZW-lijst van kankerverwekkende stoffen : Acetaldehyde,Ethyl alcohol are listed
SZW-lijst van mutagene stoffen : None of the components are listed
SZW-lijst van reprotoxische stoffen – Borstvoeding : Ethyl alcohol is listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : Ethyl alcohol is listed
SZW-lijst van reprotoxische stoffen – Ontwikkeling : Ethyl alcohol is listed

Denmark

Classification remarks : Emergency management guidelines for the storage of flammable liquids must be followed
Danish National Regulations : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Other information : None.

Full text of H- and EUH-statements:	
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2

Full text of H- and EUH-statements:	
Carc. 1B	Carcinogenicity, Category 1B
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 1	Flammable liquids, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
H224	Extremely flammable liquid and vapour.
H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H341	Suspected of causing genetic defects.
H350	May cause cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
Muta. 2	Germ cell mutagenicity, Category 2
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1A	Skin sensitisation, category 1A
Skin Sens. 1B	Skin sensitisation, category 1B
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.